

The Architecture, Design and Support of Thomson Reuters RMDS incorporating 3rd party Data feeds

John Best,
Principal Consultant KSS

1 - Introductions

- Housekeeping
- Course Tutor
- Delegates
- Rules Of Engagement
- Disclaimer
- Agenda for the Day



John Best

- 2 Years Research Assistant and Junior Lecturer, Computing Dept, Kings College London.
- 20+ Years Finance Industry Experience
 - Networks
 - Dealing Floor Management
 - Trading Systems Design
 - □ Consultancy
- Investment Banks, Brokers and Vendors
- Lives in the Lake District to escape London
- 15 Minutes of Fame Rhino Incident







Caption Competition





Disclaimer

All views in this presentation are the views of the author and not necessarily the views of his employer or his employers' clients. The author is solely responsible for any potential misrepresentations of reality.

Complaints and other feedback are most welcome, please contact:

john.best@kendaletraining.com





RMDS, Data Feeds and System Management

- This unit aims to provide a detailed breakdown of RMDS, its core components are individually assessed and their function and features investigated.
- Illustrations of functionality will be provided from a Test RMDS system
- To get the most out of this part of the course delegates should have a <u>basic</u> understanding of <u>networks</u> and <u>linux / unix</u>,



Principles Of Market Data Platform Design

- Business Drivers
 - □ Data Sources
 - ☐ Users of Data
- Technical Solutions
 - Stage 1 Data Collection & Normalisation
 - Stage 2 Data Transformation
 - Stage 3 Data Distribution
 - □ Stage 4 Data Access Control
 - ☐ Stage 5 Extending the Infrastructure




Market Data Platforms – Business Drivers

- Data Collection Prices, News and Reference Data from as many sources as possible
 - Data Feeds
 - Direct from Trading Desks
 - Trading Systems
 - Whiteboards
 - Central Data Manipulation/Transformation
- Data Storage for Analytics, Risk management and Testing Trading Sytategies and Models
 - History Database
- Data Distribution
 - Internal Systems
 - Desks via Market data display terminal and Excel
 - Other Offices
 - Clients
 - □ Web Site
 - White Labelled Display
 - Vendors
 - For fee or Attracting Order flow



Incoming Data – More than one version of the truth


Market Data System— Price Integration





Distribution Interfaces – More than one version of the truth

Market Data System— Price Distribution





Technical Solutions - Data Collection & Normalisation

- Incoming Data Feeds and Formats
 - □ Connection Types
 - **X.25**
 - Async modems etc
 - TCP/IP
 - File Transfer (Push or Pull)
 - Message parsing
 - Broadcast (with/without sequence numbers)
 - Point to Point (with/without recovery)
 - API
 - ☐ Message Payload Initial Image or Update
 - Byte stream
 - Field value pair
 - Structured object
- Feedhandler has to
 - Normalise Data
 - Maintain data integrity
 - Alert Errors



Technical Solutions - Data Transformation

- Data may not be in the form you want it!
 - Pages to Records
 - □ Records to Pages
- Simple derived calculations
 - □ Add Mid Field ie bid+ask/2
- More complex calculations
 - Average or Fair price from multiple brokers
 - ☐ VWAP from previous trades
- Delay data
 - Avoid costs
- Sample Data
 - Reduce load on down stream devices



Technical Solutions - Data Distribution

- Generate Feed
 - □ Send data to Vendor or Client
- Point to Point
 - □ Routable TCP/IP based connection
 - Access managed from Distribution Hub
- Broadcast/multicast
 - Send common data set to multiple clients
 - Client has to "play catch"
 - □ Client device responsible for recording data usage



Technical Solutions - Data Access Control

- Exchanges and other Data Suppliers
 Licence clients to use data.
 - □ Back billing for under reported usage may extend to 5 years!
 - Data suppliers undertake/commission Audits on client sites
- Any Market Data Platform must have a mechanism for recording and reporting potential and actual data usage.



Technical Solutions - Extending the Infrastructure

- Platform Technology is a key part of the bank's investment to realise commercial advantage.
 - □ Adding to the Data (API)
 - The Platform can become a key resource, housing data on the markets and securities, from an external as well as internal perspective
 - □ Using API's internally developed and 3rd party applications can leverage the Platform Knowledge base.
 - □ Adding to the Reach (WAN Gateways)
 - A Platform represents a large investment in data processing, the content can be extended to smaller offices using wide area gateways.
 - □ Cohesion (API)
 - The Platform can assist with providing the bank's systems with common pricing and reference data from a common core.



Introducing The Reuters Data Model and API

- RMDS under the Covers
 - ■Market Feed and SSL
 - □Open Message Model and RFA
- Reuters Data Feeds
 - $\square RDF$
 - □ Direct Feeds
 - □Aggregated Direct Feeds



Thomson Reuters Enterprise Platform Evolution

1990s

Triarch/TIB – src_dist / sink_dist / TIC

2000s

RMDS - MDH / P2PS / RTIC

Today


Enterprise Platform – ADH / ADS

ADH - Advanced Data Hub

ADS – Advanced Distribution Server




Real Time Data and Historical Data






RMDS 6 Components







Market Feed and SSL

- Market Feed (MF)
 - Underpins IDN Network, Marketlink, Triarch and RMDS upto V5
 - Components
 - Security Id, RIC= Reuters Instrument code
 - Field / Value Pair
 - □ **FID** = Field ID, Can be tokenised
 - □ Value in a Textual Representation
 - Appendix A
- SSL
 - SSL = Source Sink Library
 - API for developing MF based Applications



Appendix A

The Market Feed Definition

ACRONYM	DDE ACRONYM	FID	RIPPLES TO	FIELD TYPE	LENGTH	Notes
PROD_PERM	"PERMISSION"	1	NULL	INTEGER	5	Product permissions information,
RDNDISPLAY	"DISPLAYTEMPLATE"	2	NULL	INTEGER	3	Display information for the IDN terminal device.
DSPLY_NAME	"DISPLAY NAME"	3	NULL	ALPHANUMERIC	16	Expanded name for the instrument.
RDN_EXCHID	"IDN EXCHANGE ID"	4	NULL	ENUMERATED	3(3)	Identifier for the exchange on which the instrument trades.
TIMACT	"TIME OF UPDATE"	5	NULL	TIME	5	Time when the head end updated a certain field or fields in the record. Which field depends on the instrument.
TRDPRC_1	"LAST"	6	TRDPRC_2	PRICE	17	Previous last trade prices or values stack.
TRDPRC_2	"LAST 1"	7	TRDPRC_3	PRICE	17	и
TRDPRC_3	"LAST 2"	8	TRDPRC_4	PRICE	17	и
TRDPRC_4	"LAST 3"	9	TRDPRC_5	PRICE	17	и
TRDPRC_5	"LAST 4"	10	NULL	PRICE	17	и
NETCHNG_1	"NET CHANGE"	11	NULL	PRICE	17	between latest trading price or value and the historic closing value or settlement price.
HIGH_1	"TODAY'S HIGH"	12	NULL	PRICE	17	Today's highest & lowest transaction value
LOW_1	"TODAY'S LOW"	13	NULL	PRICE	17	Today's highest & lowest transaction value
PRCTCK_1	"TICK:UP/DOWN"	14	NULL	ENUMERATED	1(1)	The direction of trading from the previous trade
CURRENCY	"CURRENCY"	15	NULL	ENUMERATED	4(3)	The currency in which the instrument is quoted.




General Market Trends





Trend towards trade Automation

Algorithmic trading adoption by asset class



HF trading in equities now approaching 70% of volumes by 10% of financial institutions


(Source: Aite Group)

(Source: Aite Group)

Fragmentation in Europe:

- •118 Multi Lateral Trading Facilities (MTF)
- 58 Regulated Markets (RM)
- 23 Systematic Internalisers (SI)


Percentage of Quant-Driven Global AUM





Trend towards trade Automation

Algorithmic trading adoption by asset class




Recent analysis indicates FX trading to be at 45% automated in 2010

HF trading in equities now approaching 70% of volumes by 10% of financial institutions


(Source: Aite Group)

Percentage of Quant-Driven Global AUM





External Drivers for RMDS 6




- Direct Exchange Feeds
- Custom Exchange Feeds
 - Activ Financial
 - □ FixNetix
- New Low Latency Platform Players
 - 29 West
 - □ Skyler
 - □ Aleri

OPRA Feed Volumes



Reuters Internal Drivers for RMDS 6 and RFA 6



- Core IDN Network Capacity Upgrade
 - New Feeds
- Develop More Platform Capacity
- Driven by
 - ☐ Trends in Algorithmic Trading
 - ☐ The Quest for Speed
 - □ Programmatic access of new data types
- Extend applicability of Platform from Front to Back Office

Reuters Core Network Throughput



Break



Enterprise Platform New APIs



Open Message Model

App	Domain Message Model	Content Definition Model	Instrument Types Required Fields Field Meanings & Relationships	Product Directories	
		Item Type Model	Real World Types (Market Price, Market By Order, News, Historical, etc).	Reuters Domain Models	
RFA UPA	Open Message Model	Data	Date Containers Primitive Data Structures	Data Package	
		Transport	 Interaction Paradigms Event Model Symbology Quality of Service Entitlements 	Message Package Session Package	
	Wire Format		· Wire Encoding	Reuters Wire Format	

- Reuters Wire Format (RWF) is the physical way of expressing OMM data on the wire. RWF is not exposed to the application.
- Open Message Model (OMM) is a powerful capability that allows the representation of data using complex data structures and rich request paradigms.
 OMM is composed of Reuters SSL (RSSL), a new transport protocol, and RFA interfaces that allow the application to publish, subscribe and manipulate data
- Reuters Domain Model (RDM) is the definition of specific types of data. RDM specifies how request, response, and content messages are represented for concrete data types (e.g. Order Book).



.

Open Message Model Primitive Data Structures


OMM uses the following building blocks:

- Field List A list of field/value pairs representing a logical record
- Vector A simple integer indexed (zero based) vector of information
- Map A simple key indexed vector of information
- Series A list of coherently structured tabular information (e.g. historical data)
- Element List A list of self describing field value pairs, no dictionary is needed



Open Message Model - Data Structures cont.

- OMM containers can be nested within each other to model hierarchical data
 - ☐ Users can use OMM to create custom data models e.g.
 - Yield Curve
 - Swaps
 - Multi Asset Portfolio
 - Implied Volatility Surface
 - Others as required



 Thomson Reuters have used OMM to define a set of models called the Reuters Domain Models (RDM)

OMM Advantages

Reduced bandwidth

- 50% reduction in typical image and update size from RMDS5/MF
- 84% reduction in typical image and update size from RMDS5/TibMsg
- Increased throughput
 - 45%-100% increase in throughput, same hardware
 - Using the new ADH and ADS component of our market data system, tests scaled to 40 million updates per second
- Lowest latency
 - Fewer bytes to read, write, and send
 - Latency measured in microseconds
- Unlimited flexibility
 - Innovate new data models
 - Custom models fully supported by our market data system



OMM Advantages cont.

- Faster application processing of data
 - Faster to parse OMM messages
 - Can utilize binary data quicker in applications
- Functionality never before possible
 - Publish the QoS for the data
 - Provide responses (models) with multi-part responses
 - HTTP/HTTPS connectivity to RMDS
 - Pause and resume a stream
 - Generic Message, bi-directional generic messages
 - Private streams exclusive data exchange between a provider and consumer
 - Batch OMM item requests rather requesting items one at a time
 - OMM Dynamic views to receive just a subset of the entries
 - OMM Posting
 - OMM warm standby by using a primary and backup stream





OMM and RFA

- The Open Message Mode (OMM)
 - New Data model for Financial Instruments
 - Multiple Asset Classess
 - Real time and Reference Data
- Reuters Foundation Architecture (RFA)
 - □ Implements OMM
 - □ Backward compatibility to Market Feed (MF)
- Reuters Wire Format (RWF)
 - □ A binary implementation of RFA providing the lowest latency implementation of OMM and RFA




APIs fit for purpose – API Strategy







APIs fit for purpose - Value Add




Value Add Layers


- Ease of Use / Expanded Functionality
- Based on Features/Domains, can work with UPA or RFA
- Provide as supported libraries in each API release
- Source Code provided for Value-Add layers.
- Allows clients to build their own custom layers quickly if they don't want to use the supported ones provided.



UPA (Ultra Performance API)

The Ultra Performance API (UPA) is the first client release of the low-level internal API which is currently utilized by the Thomson Reuters Enterprise Platform for Real Time and its dependent APIs for the optimized distribution of OMM/RWF.






API General Capabilities Comparison

Capabilities			UPA	Capabilities		RFA	UPA
Transport	Compression via OMM	\checkmark	\checkmark	Domain Models	Custom Data Model Sup.	\checkmark	\checkmark
Transport	HTTP via WinINet – RWF	\checkmark	\checkmark	Domain Models	RDM – Dictionary	\checkmark	\checkmark
Transport	RV Multicast	\checkmark		Domain Models	RDM – Login	\checkmark	\checkmark
Transport	TCP/IP – RWF	\checkmark	\checkmark	Domain Models	RDM – Market Price	\checkmark	\checkmark
Transport	TCP/IP - SSL	\checkmark		Domain Models	RDM – MarkebyOrder	\checkmark	\checkmark
Application Types	Consumer	\checkmark	\checkmark	Domain Models	RDM – MarketbyPrice	\checkmark	\checkmark
Application Types	Provider – Interactive	\checkmark	\checkmark	Domain Models	RDM – Market Maker	\checkmark	\checkmark
Application Types	Provider – Non-Interactive	\checkmark	\checkmark	Domain Models	RDM – Source Directory	\checkmark	\checkmark
General Capabilities	Batch Support	\checkmark	\checkmark	Domain Models	RDM – Symbol List	\checkmark	\checkmark
General Capabilities	Generic Messages	\checkmark	\checkmark	Encoders/Decoders	ANSI Page	\checkmark	\checkmark
General Capabilities	Pause/Resume	\checkmark	\checkmark	Encoders/Decoders	DACS Locks	\checkmark	\checkmark
General Capabilities	Posting	\checkmark	\checkmark	Encoders/Decoders	Market Feed/TIB Msg	\checkmark	
General Capabilities	SnapShot Requests	\checkmark	\checkmark	Encoders/Decoders	OMM	\checkmark	\checkmark
General Capabilities	Streaming Requests	\checkmark	\checkmark	Encoders/Decoders	RMTES	\checkmark	\checkmark
General Capabilities	Views	\checkmark	\checkmark	Encoders/Decoders	TS1 Parser	\checkmark	\checkmark



RMDS 6.0


Application Compatibility





RMDS 6

Conversion Facilities



Conversion in P2PS and Source Distributor is for Level 1 data ONLY




OMM - What does it mean

- Extensible data structure for the future
 - ☐ First products RMDS 6 and RDF Direct
 - P2PS key component (universal tool!)
 - □ Retained control of market
 - □ Reduced bandwidth and latency
- Areas Of Concern
 - □ Core network Investment & Delivery
 - Project Elektron
 - Keeping display products up to date
 - V6 of 3000xtra and Eikon Workstation



Reuters Data Feed Options





3) What is RMDS and what does it do?

- Reuters Market Data System (RMDS) is a suite of software Components \that distributes Reuters Real-Time Data, and other 3rd party data which consists of many markets around the world.
- RMDS uses various network protocols (TCP, UDP and Multicast) to transfer real time market data using such application protocols Sink Source Library (SSL) and Reuters Reliable Control Protocol (RRCP).
- A well-structured RMDS environment is made up of a network topology intended to maximize availability and ensure data accuracy. The layout is designed specific to the needs of each client.
- RMDS has the ability to service multiple feeds at once, broadening the information accessibility to the clients.
- For the Reuters consolidated feed (known as IDN_RDF or IDN_SELECTFEED), information is accessed through a client application by calling in a Reuters Instrument Code (RIC). These proprietary codes are mapped by Reuters to display the appropriate information, whether it be stock or page data.

Who uses Reuters Real-Time Data?

Financial institutions such as investment banks, hedge funds, brokers, etc.



Platforms and Operating Systems

			Windows												Solaris						Linux						HP-UX				Х					
Product Category	Product	Windows 95	Windows 98	Windows NT 4 SP4	Windows NT 4 SP5	Windows NT 4 SP6	Windows 2000 SP1	Windows 2000 SP2	Windows 2000 SP3	Windows 2000 SP4	Windows 2003	Windows 2003 SP1	Windows 2003 SP2	Windows XP Home	Windows XP Home SP1	Windows XP Pro.	Windows XP Pro. SP1	Windows XP Pro. SP2	Solaris 2.5.1	Solaris 2.6	Solaris 7	Solaris 8	Solaris 10 SPARC	Solaris 10 X86	RH Advanced Server 2.1	RHEL 3.0	RHEL 4.0	RHEL 5.0	SLES 9	SLES 10	HP-UX 10.0	HP-UX 10.2	HP-UX 11.0	HP-UX 12.0	AIX 4.2.1	AIX 4.3.x
	IDB Eurobrokers Server 5.0.1								ſ	1		-							-	-		(χ						Χ	Χ		Г	т	т		_
	IDB Garban US Treasury Server 5.0	t									1										,		X			X	X*	X		X						
<u>=</u>	IDB Hilliard Farber Server 5.0							H	1	t	1	H											X				Λ*	X	X	Х				H		
2	IDB Liberty Server v. 5.0.2								i	\vdash	t	1											Х				χ*	X	X	X			H	Н		
Infrastructure Feed handler Fe	IDB Patriot Server v. 5.0	1								t		i -										-	X				X*	X		X						
8	IDB Prebon Yamane Server 5.0	t							1	\vdash	t		t									ζ	X							Х			1		\vdash	
E.	IDB Tradition Server 5.0	+								1		i										(X				X*	X		Х						
	IDB Tullet & Tokyo US Server v. 5.0	1							t	Н	1	1											X				Χ*	X	X	X			H	\vdash		
	MDH Source Infra 6.0	+		-	_			Н	1	t	+	1									ď	-		Χ			X	_	X	^	Н	H	+	H	\vdash	_
	MDH Source Infra 6.2	1						H		+	\vdash	1						1			-		X	Х	- 1		X		X							
	MDH Source Infra 6.3								-	\vdash	1	1				- 8								Х			X		X	V	Н		\vdash	\vdash		-
	MDH Source Infra 5.3	\vdash						H		┈		t						1			1		Х	Λ		Λ X*	^		Λ*	Λ			\vdash	Н		
	DTIC RMDS Ed. V. 11.1		-						-	·	-	-	-		-			-			ý		v v		X	Λ Χ*			Λ*				-	ļ	-	
- E	DTIC RMDS Ed. V. 11.1		-					-	-	-	-	-	 		-			-			- /		χ	Χ			Χ		Χ			-	-	-		
듈	DTIC RMDS Ed. V. 11.2		-						-			-			-									X			^ X		X			ļ	-	ļ	-	
Į.	RTIC v. 11.1							-	ļ	-		-	·	-	-			-			,		Х	Λ		Λ Χ*	^		Λ*				ļ	-		
8	RTIC v. 11.2								-	·	-	-	-		-			-						Х			Х		X				-	-	-	-
重	RTIC v. 11.3		-					-	ļ	-		-	ļ		-			-			-		Λ X	Λ			X		X					-		-
	P2PS 6.0		-					-	├	ļ	Χ	ļ	-		-		-	-						Λ			^ X		Χ				-	ļ		
	P2PS 6.2		-					-	+	-	X	-		-	-			-						Λ			Λ X		Χ			-	-	-	-	-
	P2PS 6.3		-						-	 	Χ	+	-	-	-			-						X						Χ		 	-	ļ	-	
	P2PS 6.3 P2PS 5.1						ļ	-	ļ		^	-	ļ										Λ X	^	X	Λ Χ*	^		Λ*	۸		-		ļ		
	DACS 5.2 <dacs-api></dacs-api>	+		_	_		v	V	V	v	+	-				v	V		Н				^						Λ		Н	H	₩	₩	Н	-
							Χ	Χ	Χ	χ	1	1				Х	٨					(_		X					Н		⊢	H	\vdash	-
	DACS 5.2 <station infra=""></station>	-					3.0	14		11/	1/	1					11	1				(١,			X	V/#		1/			1	-	<u> </u>		_
_	DACS 5.3 <dacs-api-daemon></dacs-api-daemon>	-					Χ	Λ	X	Χ	Λ	1	1	8		X	٨	-						Х			X* X*		X			-	₽	₩.	H	AK43
\$	DACS 5.3 <infra></infra>	-						H		Ł	-	1										(X					X		Н	H	₩	H		
5	DACS 5.3 <station></station>	-					2.5	1/	111	1/	110	1	1			17	110	14						X			X*		X	11	_		₩	ሥ	\vdash	-
0	DACS 6.0 <dacs-api></dacs-api>	-					Χ	X	Χ	Χ	Χ	1				Χ	Χ	X				(Х					X		Н		-	ļ.	H	1
8	DACS 6.0 <infra></infra>	-							1	-	1	-									,			Х			X	X		X			₩	₩	\vdash	-
9	DACS 6.0 <station></station>	-			10					2.7	16	1								1.5				Χ				Χ	Χ	Χ		1	⊢	ļ.	\vdash	
4	ELS v. 2.0	-		Х	Χ	X	X	Χ	X	X	X	-					X			Χ			Χ	_			X*						1	ሥ	\vdash	H
	ELS v 2.0.4							X	X	X	X	1					X					(X				X*					1	-	ļ!		
	ELS v 2.0.5	-						X	X	X	X	v	M				Χ	v					X	_			X*	- !					1	l-	\vdash	_
	ELS v 2.0.6	\vdash		17		11	2.0	Χ	X	X	Х	Х	Χ			Χ	χ	Χ	Н				χ		X Z	Χ*	Χ*				\vdash	L	Щ.	ш	ш	
	DBU 4.0	1						Χ	X	X		1										(- 1							1	-			
Value Added	DBU 4.2	1						Χ	X	Χ	1											(<u> </u>	ш	\vdash	_
P	DBU 4.2.2	1		X	Χ	Χ	Χ	Χ	X	X	16											(Χ*				8 -			_	ш	\vdash	
0	DBU 4.2.3	1				9 9				X	Χ	1											X	- 1	.	Χ	Х			9			1	\vdash		
킅	DTS 5.1	1								1_		1								Χ		(X					8 4				ш		
>	DTS 5.2.1	1)		Χ				Χ									
	DTS 5.3	1							1		1		1	18 8		1			ı				χ	Χ		X	Χ			Χ	1	1			1	



RMDS Components

Reuters Data Feed (RDF)

The RDF is managed by Reuters but hosted on the client site. The RDF is normally dual homed and serviced by a specific Reuters data center (Hauppauge, Nutley, etc) throughout the world. The RDF is responsible for servicing the Reuters consolidated feed (IDN_RDF) to Market Data Hubs at the client site.

Market Data Hub (MDH)

The MDH (also known as a Source Distributor) is hosted by the client and connects to the RDF via the Sink Source Library (SSL) to retrieve the Reuters feed data. Each MDH can publish multiple services, depending on the client's need. The MDH uses UDP Broadcast for sending data to the *Market Data Backbone*.

Point to Point Server (P2PS)

The P2PS is responsible for accepting client connections and servicing requests for the Reuters consolidated feed or any other broker service available on the network. The service published by the MDH's onto the Market Data Backbone is accessed by the P2PS via UDP Broadcast messages..

Real-Time In-memory Cache (RTIC)


The RTIC uses Multicast to deliver market data to the client application. This is used in conjunction with TIBCO Rendesvous (RV) to encapsulate the messages for the client.

Data Access Control System (DACS)

DACS is comprised of a Sybase database and several components that interact with RMDS to control what can be accessed by users in the system. This is a necessary piece of the RMDS infrastructure because it is the primary reporting system used by Reuters and most exchanges for billing and fees.



Full-scale RMDS Deployment



Thomson Reuters Enterprise Platform



Other Key RMDS Components

Inter Data Broker Feed (IDB)

IDB feed handlers provide page data from third party brokerages that use vendor specific processes to integrate into the RMDS environment using MDH servers. IDB feed handlers use serial connections directly linking to the vendor

Data Backup Unit (DBU)

The DBU is an RMDS client that provides time series data to client applications such as 3000xtra. The primary function of the DBU is to cache data from IDN in a centralized place for easy access to historical and real time information

Data Contribution Server (DCS)

DCS allows clients to make contributions the the Reuters IDN network via the service known as MARKETLINK. The DCS component can function over a serial connection or over IP.

Data Transformation System (DTS)

DTS, once known as Data Dictionary Server (DDS), is an internal RMDS application that allows users to publish and subscribe to customized data.



4) Legacy Components

- License Server
- Data Dictionary Server
- Data Publishing Server





The Enterprise License Server (AKA Effix License Server)

- □ Legacy Part of RMDS
 - Potential cause of System Unavailability
 - □ Used to protect Reuters Revenues
 - Selected Products Supported
 - □ Some RMDS applications require an Effix License Server to check the authenticity of the software running on the network. Such applications are 3000xtra version 4.5, DACS 5.3 and DTS.



м

Legacy Components (CONT)

- Data Dictionary Server
 - Aliasing
 - □ Page shredding
 - □ Replaced by DTS
- Data Publishing Server (old)
 - □ Normalises Simple Serial Data feeds
 - Mainly from Brokers



RMDS Protocols and General Configuration

- RMDS Supports a variety of Protocols
 - Client (workstation) and In-house developed data consuming applications
 - These Generally connect to the P2PS server
 - □ These connections are known as "Mounts"
 - Registered by the P2PS for Authorisation and Reporting requirements
 - □ Connections may use SSL or RFA API Libraries
 - □ Server side protocols (data sources)
 - Extant SSL source and new RFA or RWF sources supported.



A Client Connection

- IPC / SSL4
 - □ Example Config file

- RFA
 - □ Example Config file



.

IPCROUTE and RFA Configuration File

IPCROUTE File Syntax

service_name.client_type:client_host:server_host1 server_host2

Where:-

service_name triarch_sink (or rmds_ssl_sink) or triarch_dbms

client_type srclib or sinklib.

client_host hostname on which the client SSL application is running.

server_host p2ps01 p2ps02

RFA Config File Syntax

\Sessions\XtraSession\connectionList = "Connection_XTRA_SSLED"

\Connections\Connection_XTRA_SSLED\connectionType = "SSLED"

\Connections\Connection_XTRA_SSLED\PortNumber = "triarch_sink"

\Connections\Connection_XTRA_SSLED\ServerList = "p2ps01 p2ps02"



3000 Xtra


- Simplest Delivery is
 - □ 3000xtra Hosted (By Reuters / HP)
 - Massive RMDS Backbone
 - □ In this case London & Geneva
 - □ Fronted By Citrix Servers
 - □ Captive Excel Environment
 - □ Reuters manages DACS system
- Demo
 - Underlying Reuters Data structures
 - □ Feed Mapping



The DBU

Data Backup Unit (DBU)

The DBU is an RMDS client that provides time series data to client applications such as 3000xtra. The primary function of the DBU is to cache data from IDN in a centralized place for easy access to historical and real time information.





The Market Data Hub (MDH)

- Feed Handlers deliver data
- The MDH is a "Normalised Cache of All Data sources"
 - □ Implemented by multiple Backbone Protocols
 - Common Network standards TCP/IP and UDP
 - Augmented for Market Data
 - Sequencing Know if you have missed an update
 - Recovery get missed updates
 - Failover between multiple feeds
 - □ In RMDS these are
 - RRDP, RRMP, RRCP
- In actuality the Cache is a Network Switch



Source Dist

Supply side of the MDH

- □ Source Management
 - Recovery, Data quality, state management, load balancing, source mirroring, supports interactive and broadcast feeds
 - Optionally Maintains cache, auto update
 - Field and update filtering (conflation)
 - OMM, Marketfeed and ANSI Pages






Backbone Protocols

- RRDP Reuters Reliable Datagram Protocol. This protocol is used to communicate between the key Market Data Hub processes. It is made up of two protocol layers—RRCP and RRMP.
- RRMP Reuters Reliable Management Protocol. This is the market data semantics that hub components use to communicate with each other. It uses the RRCP layer for reliable end-to-end communications.
- RRCP Reuters Reliable Control Protocol. This is a transport protocol that builds reliability on top of UDP/IP. It is used to send RRMP packets between components on Market Data Hub. It is similar in function to the RV protocol.



RRDP on the Market Data Hub


OSI Layers





Data Distribution


Reuters Reliable Datagram Protocol





rrcpd

<hostname>*RRCP*nodeId







Sample RMDS.cnf file






Monitoring a Market Data Hub (MDH)

- Check for running processes (src_dist, rrcpd source & rrcpd sink Hot Standby only)
- Run src_distmon to verify operational status
- Check src_dist.log for errors or warnings.
 All service outages need investigation.



Reuters Data Feed Options







RDF Delivery

- RDF delivered as a pair of Servers
- Transmission from Reuters
 - □ X.25
 - □ Satellite
 - □TCP/IP
- Connection to Platform
 - □RFA, SSL



Reuters Integrated Data Flow







Source Monitoring

Check Connection and service availability`

Data Feed (Plus feed, RDF, Bloomberg

Feed Handler

Source Dist




The P2PS – Functionality


- One of the most important parts of the RMDS Platform
 - □ Data distribution via TCP/IP
 - □ Protocol conversion MDH4 to OMM
 - □ Support for 100's of users from 1 Server
 - □ Data Security (close coupled with DACS)
 - Tracks all data usage of connected applications
 - Well Developed Management front end



Key Components











Request Routing








Monitoring a Point to Point Server (P2PS)


- Check for running processes (p2ps, rrcpd sink, dacs.snkd & dacs.snkd slave)
- Run p2psmon to verify operational status
- Check p2ps.log for errors or warnings





m

The P2PS Server Monitor - p2psmon






User Statistics

× xterm				
Reuters	P2PS	<u>MONITOR</u>		Tue, Aug 29 18:24:55
activeSslMounts : connectionsAvailab: percentSslMountsUs:	3 100 1 99	<u>User Dat</u>	percentRsslMoun maxRsslMounts dumpDB printOutput dumpOutput disconnectStale mapSolicitedInf	: 100 : False : user.out
User Name	Maumta	List of		MaxClass
user wame ivan.buckle	Mounts 3	OpenItems 118	s MaxItems 2400	maxcrass 10
rssl.test	1	3	2400	10



Service Statistics





ĸ.


Server Statistics

×xterm RIT		P2PS MONITOR		Tue	. Sep 19	17:16:30
		. 40, 500 15 1. 15 50				
ServerName	ServerId	<u>List of Ser</u> nodeId	Load	active	pending	pendout
DCS_MARKETLINK	283	33012	0	0	0	0
GARBAN	459	33010	1	0	0	0
DDS	275	33011	0	0	0	0
TDQFS	291	33011	0	0	0	0
IDN_SELECTFEED	271	33008	1	0	0	0
IDN_SELECTFEED	273	33009	1	277	0	0
IDN_RDF	45000	50005	296	753	0	0




Monitoring a Reuters TIC (RTIC)

- Check for running processes (rtic & rvd)
- Run rticmon to verify operational status
- Check rtic.log for errors or warnings.
- Visit the RVD website (default port 7850) for additional statistics and subscriptions.





P2PS and DACS







Data In

MDH and RDF

- □ RDF connectivity
- □ Source Distributor Monitoring,Troubleshooting and Maintenance




The DACS

- □ Functionality
- □ Components
- □ Operation




P2PS and DACS





DACS Username - where does it come from?






Running the DACS UI

To start the DACS UI, click Start -> Programs -> DACS -> DACS Station Console

The default username/password: reuter / p_reuter






Importance of Data Transparency & Compliance

- Meeting contractual obligations with content providers
- Ensure the right users are receiving the right data on every application
- Ensure accountability and create an audit trail for administrator changes
- Need for cost optimisation
- Simplify administration and management



Environment





Comprehensive Entitlements Solution

DACS Product Suite

DACS

System - The most complete and widely accepted entitlement solution in the industry

Open DACS

API - Extend
entitlements
solution beyond
the traditional
market data
distribution system

Open DACS Permission Server


Permission
Server – Simplify
the way to
incorporate
entitlements into
applications

DACS On-Demand

Automated entitlement control to eliminate excess spend and reduce data spend per user / application to only what is truly needed




Applying the Solution






Open DACS





Open DACS Permission Server



DACS on Demand

- A capability that enables the pro-active management of data entitlements
- Provides the necessary transparency to reduce total expenditure on data fee liabilities
- Only those entitlements that are needed will remain active

Delivering a large cost saving potential



9) RMDS "hands on" Management

- □ General Maintenance and Administration Tasks
- □ Key Monitoring Utilities
- □ Troubleshooting Tips
 - Instrument & feed failure
 - User data issues
 - Using Unix commands for Diagnostics
 - Using the P2PS Monitor



General Maintenance and Administration


- Basic Unix Utilities
 - □ Server Resources
 - Memory
 - Diskspace
 - CPU Utilisation
 - □ Network & Overall Platform Performance
 - Network Component Monitoring
 - □ Corvil
 - □ TipOFF
 - □ SNMP Agents



Monitoring General System Resources

- vmstat reports cpu, memory and swap utilization
- free reports memory utilization
- uptime reports system uptime and load averages
- dmesg shows recent system messages
- netstat -ni shows interface packet counts, errors and collisions
- netstat -an shows all active network connections
- dladm show-dev (Solaris 10 only) reveals network interface speed/duplex
- ethtool <device> (Linux only) reveals network interface speed/duplex
- ps aux (Linux) (Solaris 10, located in /usr/sfw/ps) shows all processes running including cpu and memory utilization
- ps -ef shows all processes running





How do I tell if Hot Standby is enabled?

- Running src_distmon on the IDN MDH, check the servers section. The service should have a 5 digit serverId (i.e. 45000) as opposed to a normal 3 digit serverId (i.e. 280).
- In addition, check the Hot Standby statistics to determine what state the MDH is currently running in (Active, Active/Peer or Standby)



A service is reporting as "DOWN", now what?

If IDN_SELECTFEED is reporting down, check the src_dist.log to determine when the problem started. The log will normally report two types of outages:

"Data feed links are bad"

The RDF lost its TCP connection to Reuters. This is usually indicitive of a problem upstream, such as an RSS failure or bandwidth overutilization.

"Loss of channel"

The MDH lost its TCP connection to the RDF. This is usually an internal network problem, but problems with the RDF itself can cause the channel to be cut resulting in such an error.





Recognising and Troubleshooting Basic Problems (2)



An item (or multiple items are stale), what can I do?

- If multiple items are stale, be sure to check the RMDS environment health for any network issues or system utilization that could be effecting the binaries.
- Reuters issues alerts (RIC: ALERTS) signifying any problems currently being experienced at their ticker plant. These issued reactively and proactively by Reuters on a regular basis.
- Check against another site to ensure the issue is not a global problem. If the issue exists elsewhere, call Reuters support to inform them of the issue.







Trouble shooting (3)

- User(s) are unable to mount.
- Check the network connectivity to the user's workstation. Have the user run "ping" to the P2PS (will only work if ping is enabled on the network). In addition, the user can run "telnet" to port 8101 to verify the P2PS is responding.
- Have the client check the ipcroute file on the workstation to verify the network configuration is correct.
- If a user is unable to mount to a DACS enabled P2PS, check the DACS Station to ensure the user is configured properly to receive data. Be sure to verify the user's simultaneous mount limit has not been reached.
- Running p2psmon, verify the P2PS mount limit has not been reached. If the connection limit has been reached, have the user connect elsewhere.
- Double-check the DACS servers to confirm they are operational and DACS is active.




Managing Users on a P2PS

- System Mangers should keep a constant watch on P2PS loadings,
 - ☐ # mounts
 - □ # cache items
 - CPU load
- The most common cause of user complaints about data quality and speed of update is an over loaded P2PS
- Symptoms
 - Visible update differences for same instrument on different workstations
 - □ Some users unable to connect intermittently
- Techniques for resolution
 - Profiling users
 - □ Pooling P2PS's into groups
 - Be very careful with gold builds!









10

Key Monitoring Utilities

- ITRS
 - □ Widely Used 3rd Party system Monitoring
- Hawk
 - Reuters Licensed Monitoring tool
 - Supplied by TibCO
- Sentinel+




10) Performance Test Results

- IBM Initial Benchmarking
- Red Hat
- Solaris



Stac Testing 2007







Stac testing 2008

- RMDS 6
- RHEL 5.1
- IBM Blade Centre H
- 10 Gb Ethernet Switch
- Chesio 10 GB Ethernet card



Results

- 1. Lowest mean latency ever reported with RMDS
 - □ Less than 0.9 milliseconds of end-to-end infrastructure latency at up to
 - □ 600,000 updates per second in the low-latency configuration of RMDS
- 2. Lowest standard deviation of latency ever reported with RMDS
 - □ Less than 0.5 milliseconds at rates up to 600,000 updates per second.
- 3. Very high output rate in the
 - □ 5.8 million updates per second
 - □ 30% of this due to the TCP/IP Offload Engine (TOE) in the Chelsio NIC Blade Network Technologies 10GigE Switch




w

Red Hat Test Environment

- RMDS6
- RRCP
- Redhat Enterprise Linux 4/5
- Intel Xeon (x86-64)
- 1 Gb Ethernet



Test Results







Summary

- In the configurations tested, there is no statistically significant performance regression when going from RMDS 6 / RHEL 4.4 to RMDS 6 / RHEL 5.1
- Process and Interrupt binding to cpu cores did not make any appreciable difference in performance
- Setting TSO to "on" and "off" did not make any appreciable difference in performance





Other Options TSO

- TCP Segmentation Offload (TSO) is used to reduce the CPU overhead of TCP/IP on fast networks. TSO breaks down large groups of data sent over a network into smaller segments that pass through all the network elements between the source and destination.
- This type of offload relies on the NIC to segment the data and then add the TCP, IP and data link layer protocol headers to each segment. The NIC must support TSO.
- [TSO is "off" by default in RHEL 4.4 and TSO is "on" by default in RHEL 5.1]





Interrupt Binding

- Tests have shown that there is less fluctuation in the update rate if the RMDS infrastructurecomponents are bound to individual CPU(s).
- In addition to such binding, Reuters has found that binding NIC interrupts to a single CPU helps achieve better CPU utilization on the System Under Test (SUT) node(s).
- [By default, on a dual NIC dual CPU SUT node, interrupts from eth0 are bound to CPU 0 and interrupts from eth1 are bound to CPU 1.]






Sun Reccomendations (2009)

- RMDS 6
- Solaris 10 x86
- Sun Fire 4170 (Xeon)
- Solaris Containers



Small Site with Containers








Small site HW

- RMDS 6 Components Hardware Model Number of CPUs Memory Disk
- Source Distributor, P2PS, DACS Server and RMS
- Sun Fire X4170 2 x QC Intel Xeon E5520
 4GB 2 x 146GB



Large Site (>500,000 rics, 256 users)







Large Site HW

- Source Distributor and DACS Server / RMS
 - Sun Fire X4170 2 x QC Intel Xeon E557012GB 2 x 146GB
- P2PS and RTIC
 - Sun Fire X4170 2 x QC Intel Xeon E557012GB 2 x 146GB



ĸ,

Pushing the Limits (RHEL)

- 1. Highest Source Distributor throughput to date on a single 4-socket or 2-socket server
 - □ 2.8 million updates per second
- 2. Highest Point-to-Point Server throughput to date on a single 4-socket or 2- socket server
 - 2.2 million updates per second through a single Point-to-Point Server
- http://www.STACresearch.com



11) System Tuning

- Single threaded components
- New Multi-threaded RMDS Components
 - □ ADH Advanced Data Hub
 - □ ADS Advanced Data Server
 - □ ATS Advanced Transformation Server
- User Load Balancing for Performance
- Performance Test Results



Single Threaded Applications

- First Generation of RMDS components are single threaded
 - □ Reuters recommended single applications to be run on single cpu servers
 - Note stability and performance of RMDS backbone can be compromised by a single poorly performing server
 - □ Where multiple cpu or cores are available then virtualisation can be used to increase performance



Advanced Data Hub

- Basically a multithreaded version of the Source distributor
- Able to handle higher capacity and updating feeds
 - □ Eg OPRA
- Supports new OMM data model





Advance Data Server

- Multithreaded version of P2PS
 - One thread used for interfacing to MDH
 - One thread allocated to each client connection



Advanced Transformation Server


- Major Rewrite of DTS incorporating functionality from
 - □ DTS Existing features
 - □ Gissing Page Building/Shredding
 - □ Vhayu Advanced Calculations
- Output in OMM formats
- Redesigned user interface



Enterprise Platform Scalability Performance




Scalability Performance - Distribution





Scalability Performance - Backbone





KSS © 2011 Caching Disabled

Under the covers

- The New Reuters API
 - $\square RFA$
 - □ Legacy support
 - □ Direct Feed Connections



Break



Review Data Model Terminology

■ Data Model Definition The solution is ...


Reuters Domain Model	Content Definition Model	■Field Meanings ■Field Relationships				
	Item Type Model	■Real World Objectives (i.e. Quotes, Order Books, etc).				
Open Message Model	Data	Data ContainersPrimitive DataStructures				
	Transport	Interaction ParadigmsSymbologyQosEntitlements				
Wire Format		■Wire Encoding				

- Reuters Wire Format (RWF) is the physical way of expressing OMM data on the wire. RWF is not exposed to the application.
- ■Open Message Model (OMM) is a powerful capability that allows the representation of data using complex data structures and rich request paradigms.
 - OMM is composed of Reuters SSL (RSSL), a new transport protocol, and RFA interfaces that allow the application to publish, subscribe and manipulate data
- ■Reuters Domain Model (RDM) is the definition of specific types of data. RDM specifies how request, response, and content messages are represented OMM for concrete data types (e.g. Order Book).



RFA 6

RFA Utilities



RFA Session Layer														
(DMM		Market Data Pub / Sub					RV API						
F	RSSL			SSLe dapt		STIC Adapter	SASS Adapter Adapte			IFP Adapter	Arı			
RDFDirect 1.2	SrcDist 6	7 4 7 0 0	D)D0 6	Sink Dist	Src Dist	STIC	TMF	DTIC	TIC	RTIC	RDTIC	RSS	RVD	



RFA 6.0


Platform Support

SOLARIS	Solaris 10	SPARC
SOLARIS	Solaris 10	x86
redhat	Red Hat	AS3/4
Windows Server 2003	Windows	Windows 2000 & XP



RFA C++ 6.0

New Interfaces & Capabilities



RFA C++ 6.0 provides...

- New OMMConsumer and OMMProvider interfaces
- ■New Request and Response classes
- ■New Encoders/Decoders for OMM
 Primitive Data Structures
- RFA5 interfaces to provide compatibility with existing applications and interoperability with new OMM interfaces. STL references are being removed from RFA5 interfaces, which may require some minimal application changes.
- ■Performance and latency enhancements
- Symmetric messaging paradigm
- Direct Connect capabilities



13) Examples of 3rd Party data Feeds

- Limitations
- 3rd Party Feeds Available
- Using data in 3000xtra and Excel



Limitations and Cautions With 3rd Party Data Feeds

- Representation in Reuters Terminal Products
 - □ Templates!
- Mapping of data to Market Feed
 - □ Limitations of FID Lists
 - Extensions of FID lists




Direct Exchange Feeds

- Most Exchanges offer Direct Feeds
 - □ At a Price!
 - □ Aimed at Alogo and DMA trading activities
- Major Feed Handler Suppliers
 - □ Reuters
 - NYSE Technologies (Wombat)
 - □ InfoDyne (IBM)




Differences Between Vendors 1





Differences Between Vendors Delivery



Direct v Composite Feed on LSE - Direct is the baseline and Composite is on avg 250ms slower



×

Aggregated Feeds




Bloomberg Feed Options Summary

Other Data Sources


- Two Approaches
 - □ Bloomberg Server API
 - Full Content
 - Limited Capacity
 - □ Bloomberg Feed
 - Low Latency
 - Exchange Content

Arcontech	www.arcontech.com
Bloomberg	www.bloomberg.com
Infodyne	www.infodyne.com
Reuters	www.reuters.com
Wombat	www.wombatfs.com





B-Pipe Components





IDC Plus Feed

- Low Latency
- □ Global Exchange Coverage
 - Also OTC, News
- □ Delivered as a server on Site
 - Dell R610
- Optional
 - Delayed Data Options
 - Normalised Data
- □ Handlers available for/from
 - Interactive Data Managed Solutions
 - Interactive Data Real Time Services
 - Arcontech / RMDS
 - TS Associates /RMDS
 - Wombat / RMDS





Six Telekurs



Historically

- End Of Day Pricing Service
- National Naming Authority for Switzerland
- All ATM's & Card Payment systems In Switzerland
- Now Merged with Swiss Exchange & Clearing Services

Latest Products

- Valordata feed
 - Mifid Focus
 - □ Financial Instruments Data Model (FIDM)
 - □ > 7m Securities
 - □ Interest list or Market interest driven
- Telekurs Market Feed
 - Real Time Data Feed
- □ Terminal Product
 - Telekurs ID



.

Dow Jones

- Index Business sold off to CME
- Frustrated recently by loosing prime routes to market for news services
 - □ Telerate, Bridge, Thomson
- Still available on Reuters, Bloomberg, IDC etc.
- Now Distribution is also
 - □ Direct via BT, Savvis
 - □ Over Internet
 - □ Tradition wire services
 - □ RSS feeds
- Flagship product
 - Dow Jones Elementised News Feed



r,

Factset - Marquee

- Poor Mans Bloomberg!
 - Research
 - Analytics
 - Pricing
- Terminal business shown steady growth over last 5 years
- About to enter Feed Business





SunGard

- Massively Comprehensive Front Middle and Back Office system supplier
 - □ Feed
 - Platform
 - Analytics
 - □ Time series Database
 - Trading
 - Settlement
- Currently in process of rationalising and merging its assets
- Partnered with SixTelekurs for real-time datafeed content (FAME)



Other Alternate Data Feeds

- Fidessa
 - □ About 90 exchanges
 - □ Custom Feed Packages
 - □ Cost + Pricing model







Specialist Bespoke Feed Suppliers

- ActivFinancial
- Quant House
- FixNetix





Real World Challenges for Data Feed Replacement

- Target Replacement Usage
 - Workstations
 - □ Excel
 - □ Applications
- Tools to Assist Replacement
 - □ Dacs Reports
 - □ Spreadsheet Sniffers



Workstation Challenges

- User Familiarity with new Symbology
- Data Representation in Alien Workstations
 - □ Is it Allowed?
 - ☐ How does it Look
 - Templates
 - Field Cross mapping
 - □ Cross linkages
- Tools and Assistance ?



Excel

- Can data be accessed?
 - □ Default Data Source
- Existing spreadsheets
 - Changing spreadsheets is challenging
 - Do they still work
 - What if a record/field is not mapable
 - Identifying sheets to be changed





- So long as symbology and fields are user definable then relatively easy.
 - Note some systems assume Reuters rics etc.
- Case study
 - □ BGC replaced Reuters Rics in Gloss (equities trading platform) with IDC Plus Feed
 - saved 30% on data costs
 - Clearer Licensing agreement



Tools

- DACS Reports
 - □ Exchange utilisation by user
- P2PS Cache
 - □ Instrument lists
- Spreadsheet sniffers
 - Last Used
 - □ Addins
 - External links
 - □ Case studies Lehmans and Citi Group



14) Publishing Excel and Contributions

- Excel for Display of Realtime Data
- Excel For Publishing
- Contributions to Vendors



Don't Forget Excel

- Excel in Front Office
 - > 91 % New business analysis and support
 - > 89 % Investment appraisal
 - > 82 % New Product/Investment creation
 - > 82 % Position Management
 - > 91 % Pricing and Valuation
 - > 75 % Risk and/or Portfolio simulation
 - 79 % Risk calculation
- Excel in Mid and Back Office
 - > 75 % Management Reporting
 - > 89 % Financial Reporting and analysis
 - > 67 % Post trade revaluation
 - 86 % Data aggregation
 - > 80 % Reconciliation
 - > 62 % Risk and portfolio simulation
 - > 78 % P&L Calculatio

Source - Waters Magazine

Figures show % IT and Business Respondants indicating Frequent or Very Frequent usage of Excel

For Critical Business Functions






Next Generation Excel

- Excel V 12 (Office 2007/10)
 - Bigger Grid
 - Multi Threaded
 - > RTD Engine
 - New Graphics Engine (from Office 2007)
- What does this mean
 - Handles More Input Data
 - Generated output faster
 - More complex models can be run
 - Doesn't crash as easily!
 - Interoperability with Other Office Products
- The Trader's Desktop/Workstation of Choice



KSS Testing Initial Findings




- Software tested
 - Arcontech Excelerator
 - Gissing RealTime Excel
 - □ PowerPlus Pro
- Latency Measurement Software
 - JPA DataQA

- Findings
 - Significant reduction in throughput delays
 - Increased number of Ticks Found!
 - □ Additional CPU's effectively used
 - RTD not fastest method
 - XLA most performant
 - Data tables preferable




Excel 12 Size






Excel 12 Threads






Excel 12 New Charts Rendering






Excel 12 New In Cell Features






Gissing Excel Add-in



Reuters Regional Data Collection








Excel 12 Case study (a large European Broker)

- > Requirement
 - Increased update Rate on outbound IRS data to vendors
 - > USD, Euro and GBP
 - Keep Flexibility of Spreadsheet Approach
 - Don't write dedicated application
- Known Issues
 - Spreadsheet Stability
- Baseline Exercise
 - Update rate comparison between 4 leading brokers
 - > On Reuters
 - On Bloomberg




Existing Infrastructure





Low Latency Infrastructure





Spreadsheet Exposure

 To What extent does spreadsheet usage fall within your current regulatory initiatives
 (Survey UK IT Finance Sector Directors - Waters)

Regulation	Significant + Moderate	Significantly	Moderate	Some	None
Basel II	88	63	25	12	0
FSA compliance	67	56	11	22	11
Operational Risk	89	44	45	11	0
MiFID	63	38	25	12	25
sox	75	25	50	25	0



15 New for 2011

- Thomson Reuters
 - □ Recent Developments
 - Project Eikon
 - Project Elektron
 - Thomson Reuters Enterprise Platform



Project Eikon

- Official name for Previous Utah Project
 - □ New common user data presentation environment for all Thomson Reuters Workstation Products
 - 2010 Merges some existing Reuters products
 - □ 3000Xtra, Trader, Wealth Manager
 - □ Status Customer Beta as at Q1 2011
 - **2011**
 - □ Reuters Knowledge
 - **2012**
 - Thomson One



Project Elektron

- Renewal of Thomson Reuters Infrastructure
 - Collection
 - Direct Exchange Feeds
 - Full order book supported
 - Client Data (Contributions) via Gissing Software
 - Replaces
 - OCS, DCS
 - Marketlink
 - Marketlink IP
 - Distribution
 - Regional Hubs and Reduced Number of Data Centres
 - Mergers Reatime and Reference data distributiom
 - Ultimately Replaces IDN, RXN, BDN and TDN as main Distribution Networks






Thomson Reuters Enterprise Platform Versions

- TREP for Real Time
 - □ Upgrade to RMDS
- TREP for Analytics and Trading
 - Pricing
 - □ Tick storage
 - Interfaces to Order Routing and Execution services.
- TREP for Reference Data
 - Multi source storage and aggregation of Reference Data
 - Leverages Ex Thomson and Reuters Ref Data feeds and 3rd parties.
 - Data management with change control
 - Incorporates real time for evaluations




Client Environment





The Enterprise Platform for Real-Time








Thomson Reuters Enterprise Platform Versions

- TREP for Reference Data
 - Multi source storage and aggregation of Reference Data
 - Leverages Ex Thomson and Reuters Ref Data feeds and 3rd parties.
 - Data management with change control
 - Incorporates real time for evaluations




Information Services Framework



Empowers critical downstream business processes using flexible data services



Enterprise Platform components



Promotes accuracy, transparency and efficiency by standardising on a market standard data model



Enterprise Platform - Logical Architecture

Role-based User Interfaces

(data management, business integration, systems administration, business analysis)









Plug-in
Data Feed
Handlers
(real-time, reference,
historical)




Plug-in
Data Management
Repositories
(reference, pricing,

(reference, pricing, entities, transactions)

Enterprise & 3rd Party Plug-ins








Enterprise & 3rd Party Applications




Reuters Enterprise Platform in more detail





Reuters Market Data System

- Industry leading platform for high throughput real-time market data distribution
 deployed at 2,800+ sites globally
- Robust Application Programming Interface –
 Reuters Foundation API (RFA) extends support for diverse data types
- Open Message Model (OMM) allows representation and transmission of complex data structures with rich request paradigms




- Powerful modules can be introduced incrementally
 - User connectivity to desktops, browsers and wireless devices
 - Configurable filtering, integration, enrichment and analytics
 - Adapters to diverse information sources and contribution facilities






- Reference Master Database with an extensible data model that conforms to market data standards
- Integrates consolidated referential data from a wide array of the industry's most trusted vendors – more than 150 feeds from 18 vendors
- Integrates silo'ed referential data within the enterprise



- Centralised hub for rule-based data acquisition, cleansing, validation, enrichment, scrubbing and normalisation
- Extensive and adaptable user interface supports manual creation of data, data quality rule generation, decision trees and search
- Full user and feed management capabilities with built in reporting and exception handling



RRDS Logical Architecture and Data Flow






Reuters Enterprise Integration Engine


- Reuters Enterprise Integration Engine
 - □ **Integrates** RMDS and RRDS components to consolidate all data assets through a market standard holistic data model
 - Orchestrates data services and manages service operations with effective exception handling and reporting
 - Delivers context specific data views without compromising the integrity of the underlying data
- Component based approach
 - ☐ Ensures **interoperability** with existing systems architecture and avoids 'rip and replace'
 - □ Recognises **unique technical requirements** in support of real-time and non-real time data (persistence, transport etc.)



REIE Layered Architecture









Thomson Reuters Enterprise Platform


- Enables business users and applications to share accurate,
 consistent, and timely data assets
- Leverages Reuters extensive and **well-proven** data delivery capabilities (RMDS) and developer community programmes (RDC)
- Addresses new and changing business needs by empowering critical downstream processes using flexible business data services
- Promotes transparency and efficiency by supporting a hierarchy of reusable and adaptable platform data services
- Exposes instrumented data services that support business-led metrics and benchmarking
- Supports incremental deployment to deliver immediate return on investment and durable business transformation



ENTERPRISE PLATFORM – Beyond Market Data



Client Environment





Market Connect


- Provide integration within the enterprise using private streams and generic messaging
 Single platform that enables market data and transactional communication between front, middle and back office systems.
 Capability to onboard new clients using the platform without developing new gateways/networks
- **□ OMM Private streams**
 - □ One-to-one client server communications
- □ OMM Generic Message
 - Bi-directional data type agnostic messaging capability




Enterprise Platform Latency Performance



Latency – Right time delivery




Latency – Right time delivery





Tier 0



Local Remote





References



Additional Sources: Jack Gidding, Dan Huckle, Dan Solack, Gareth Rees, JP Carbonier,





Q & A